

SRSC45E5

SANY Electric Reach Stacker



1

Higher safety standards

- Products obtained EU CE certification
- With high voltage interlock function, real-time monitoring of high voltage circuit is complete. Prevent faults that are believed to be caused by improper operations.

2

EMC Certification

- The high-voltage and low-voltage wiring harnesses are arranged in layers to reduce the interference of high-voltage signals, and the equipment runs more reliably. The product has passed EMC certification.

3

Optional charging port



- Optional CCS1 and CCS2 charging port to meet the needs of users in different regions.

► Product Parameters

Technical Parameter		
ITEM	UNIT	SRSC45E5
Max. Lifting speed (0/full load)	mm/s	420/250
Max. Lowering speed (0/full load)	mm/s	360/300
Max. Traveling speed (0/full load)	km/h	20/14
Gradeability (0/full load)	%	21/14
Hydraulic system working pressure	bar	340
Overall weight	t	73
Rated load	t	45
Stack layer	-	5
Max. Lift height standard	mm	15100
Max. Boom elevation	deg	0-60
Overall length L	mm	11320
Wheel base L1	mm	6000
Overall height H (retract/extend)	mm	4850
Min. Ground clearance H1	mm	330
Overall width W	mm	6053-12185
Counterweight sideways E	mm	-
Front gauge T1	mm	3033
Rear gauge T2	mm	2790
Min. Turning radius R	mm	8000
Aisle width for 20'container A1	mm	11300
Aisle width for 40'container A2	mm	13600

Configuration Parameter		
CONFIGURATION	UNIT	SRSC45E5
Energy type	-	Electric
Charging time	min	90
Endurance time	h	6/8
Quantity of electricity	kWh	422/507
Traction battery	Battery type	-
	Standard voltage	V
	Thermal management	-
Electric motor	Type	-
	Output torque (Rated/peak)	Nm/rpm
	Output power (Rated/peak)	kW
	Output rotate speed (Rated/peak)	RPM
	Cooling type	-
Transmission type	-	Kessler d102

► Dimensions



PT SOLUSI INDO PERDANA

BE PRODUCTIVE, BE SOLUTIVE FOR MATERIAL HANDLING

Head Office :
Ruko Pesona Gintung Residence, Blok AA No. 06, Cempaka Putih, Ciputat Timur, Tangsel 15412

Branch Office :
Jl. Sultan Hasanudin KM.41 No. 2 Blok E24, Tambun, Kec. Tambun Selatan, Kab. Bekasi – 17510

Email :
sales@alatberatsip.co.id

Hotline Service :
(021) 7433477 / 087720101020